


# Anchor Windlass

## Single Horizontal Anchor Windlass

- Custom Engineered Units
- Chain Sizes 3/4" to 2 1/2"
- Designed per ABS Grade 3 Anchor Chain Rules
- Electric or Hydraulic Motor with failsafe brake
- Fully Enclosed Planetary Gearbox
- Band Brake
- Jaw Clutch
- Chain Stripper
- Optional Features:
  - Capstan Head
  - Chain Stopper



Model No.	Chain Size (inches)	HP	Line Pull (lbs.)	Hoisting Speed (≈fpm)
SHAW-0.75-7.5	3/4"	7.5	5,800	30
SHAW-0.875-7.5	7/8"	7.5	7,900	30
SHAW-1-10	1"	10	10,300	30
SHAW-1.125-15	1 1/8"	15	13,050	30
SHAW-1.25-15	1 1/4"	15	16,100	30
SHAW-1.375-20	1 3/8"	20	19,500	30
SHAW-1.5-25	1 1/2"	25	23,200	30
SHAW-1.625-30	1 5/8"	30	27,225	30

Model No.	Chain Size (inches)	HP	Line Pull (lbs.)	Hoisting Speed (≈fpm)
SHAW-1.75-30	1 3/4"	30	31,575	30
SHAW-1.875-40	1 7/8"	40	36,250	30
SHAW-2-40	2"	40	41,250	30
SHAW-2.125-50	2 1/8"	50	46,550	30
SHAW-2.25-50	2 1/4"	50	52,190	30
SHAW-2.375-60	2 3/8"	60	58,150	30
SHAW-2.5-75	2 1/2"	75	64,450	30

All dimensions are in inches and are subject to change.

